

SPTO 1250

SPECIFICATIONS

	U.S.	Metric
Concrete Output Per Hour	95 cu yds	73 cu m
Maximum Pressure on Concrete	942 psi	65 bar
Maximum Aggregate Size	1.5 in	37 mm
Concrete Cylinder Diameter	7 in	180 mm
Concrete Cylinder Stroke Length	55 in	1400 mm
Differential Piston/Rod Diameter	3.15/ 2.16 in	80/ 55 mm
Outlet Diameter	5 in	125 mm
Concrete Valve Type	Long Rock™	
Shifting Cylinders	2	
Max. Pump Strokes Per Minute	34	
Volume Control	0 to Maximum	
Hydraulic System	Open Loop	
Main Hydraulic Pump	A11VLO130	
Hydraulic Pressure	4785 psi	330 bar
Hydraulic Tank Capacity	98 gal	371 l
Engine Model- Diesel Tier 3	CAT 6.6 TA-ECU 2200 RPM	
Engine Power	174 hp	129.5 kW
Fuel Tank Capacity	50 gal	189 l
Hopper Capacity	11 cu ft	.31 cu m
Remote Control Cable	100 ft	30.5 m

*Pump specifications are for standard units. Other units are available.
Specifications are subject to change without prior notice.

